



DECLARATION OF PERFORMANCE – Cementfill FC

1. Identification code: **Class R4 PCC mortar. Waterproof screed, fairing coat and pore filler.**
2. Serial number: **Cementfill FC**
3. Intended use: **Typically used to fill blow holes and defects, repairing surface cavities and honeycombed concrete. Thin screed application to both vertical and horizontal surfaces and to reinstate concrete over.**
4. Manufacturer: **RIW Limited, ARC House, Terrace Road South, Binfield, Berkshire RG42 4PZ**
5. Authorised representative: **Not applicable**
6. Assessment and verification of constancy of performance: **System 2+**
7. Relevant harmonised standard: **EN 1504 – 3 : 2005**

Factory Production Control Certificate Number 0086-CPR-597751

8. European Technical Assessment: **Not applicable**
9. Declared performance

Essential Characteristics	Performance	Harmonised Standard
Carbonation Resistance	Passes	EN 1504 – 3 : 2005
Adhesive Bond	R4 ≥ 2.0 MPa	
Compressive Strength	R4 ≥ 45 MPa	
Chloride Ion Content	≤ 0.05%	
Thermal Compatibility	R4 ≥ 2.0 MPa	
Capillary Absorption	≤ 0.5 kg m ⁻² h ^{-0.5}	
Elastic Modulus	R3 ≥ 15 GPa	
Restrained shrinkage / Expansion	NPD	
Dangerous Substances	Complies	
Reaction to Fire	Euroclass A2-s ₁ , d ₀	

Specific Technical Documentation: **Not applicable**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Martin Radford (Business Manager)

