

Safety data sheet
according to 1907/2006/EC, Article 31

Printing Date: 31.01.2020

Version Number: 1.0

Revision Date: 31.01.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier:**Trade name: *RIW FLEXISEAL 500 HG (W)***1.2 Relevant identified uses of the substance or mixture, and uses advised against:**

Identified uses advised against: No further relevant information available.

1.3 Details of the supplier of the safety data sheet:**Manufacturer/supplier:**

RIW Limited
580-581 Ipswich Road,
Slough, Berkshire
SL1 4EQ

Tel: +44 (0)1753 944210

www.riw.co.ukFurther information obtainable from: enquiries@riw.co.uk**1.4 Emergency telephone number:**

For Chemical Emergency: (Spill, Leak, Fire, Exposure or Accident) - Call CHEMTREC (Day/Night) on:

Within USA & Canada : 800-424-9300,
Outside USA & Canada : +1 703-741-5970

National emergency telephone number: CHEMTREC UK +(44)-870-8200418

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture:****Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements:**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

Methyl methacrylate

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing Date: 31.01.2020

Version Number: 1.0

Revision Date: 31.01.2020

Trade name: RIW FLEXISEAL 500 HG (W)

(Contd. of page 1)

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P362+P364 Take off contaminated clothing and wash it before reuse.

Hazard description: Flammable**2.3 Other hazards:****Results of PBT and vPvB assessment:****PBT:** Not applicable.**vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterization: Mixture:**Description:**

Mixture of substances listed below with non-hazardous additions.

For further information, please refer to the product technical data sheet.

Dangerous components:

CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6 Reg.nr.: 01-2119452498-28- XXXX	Methyl methacrylate Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	25-<30%
CAS: 38668-48-3 EINECS: 254-075-1 Reg.nr.: 01-2119980937-17-XXXX	1,1'-(p-tolylimino)dipropan-2-ol Acute Tox. 2, H300 Eye Irrit. 2, H319 Aquatic Chronic 3, H412	0.1-<1%

SECTION 4: First aid measures

4.1 Description of first aid measures:**General information:** Get medical advice/attention if you feel unwell.**After inhalation:** IF INHALED: Remove person to fresh air and keep comfortable for breathing.**After skin contact:** Wash with plenty of soap and water.**After eye contact:** Rinse cautiously with water for several minutes.**After swallowing:**

Rinse mouth.

Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed: May cause sensitisation by skin contact.**4.3 Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media:**Suitable extinguishing agents:** CO₂, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.**For safety reasons unsuitable extinguishing agents:** Water jet.**5.2 Special hazards arising from the substance or mixture:** No further relevant information available.

(Contd. on page 3)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing Date: 31.01.2020

Version Number: 1.0

Revision Date: 31.01.2020

Trade name: *RIW FLEXISEAL 500 HG (W)*

(Contd. of page 2)

5.3 Advice for firefighters:

Protective equipment: Wear self-contained respiratory protective device.

Additional information: Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures:**

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling:**

Flammable mixtures with air can be formed in emptied containers. Do not puncture, cut, drill, heat or weld uncleaned drums.

Do not eat, drink or smoke when using this product.

Store in a well-ventilated place. Keep container tightly closed.

Keep only in original packaging.

Use only outdoors or in a well-ventilated area.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ground and bond container and receiving equipment.

7.2 Conditions for safe storage, including any incompatibilities:**STORAGE**

Requirements to be met by storerooms and receptacles: Store in a cool location.

Further information about storage conditions:

Keep container tightly sealed.

Protect from frost.

Store in a dry place.

Keep cool.

7.3 Specific end use(s): No further relevant information available.

GB

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing Date: 31.01.2020

Version Number: 1.0

Revision Date: 31.01.2020

Trade name: **RIW FLEXISEAL 500 HG (W)**

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters:

Ingredients with limit values that require monitoring at the workplace:

80-62-6 Methyl methacrylate

WEL	Short-term value: 416 mg/m ³ , 100 ppm
	Long-term value: 208 mg/m ³ , 50 ppm

PNECs

80-62-6 Methyl methacrylate

PNEC freshwater	0.94 mg/l
PNEC marine water	0.094 mg/l
PNEC soil	1.47 mg/kg

Additional information: Based on the lists valid at the date of SDS creation.

8.2 Exposure controls:

PERSONAL PROTECTIVE EQUIPMENT

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Respiratory protection:

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate for the listed ingredients. (NIOSH, CEN, etc.).

EN 143.

Protection of hands:

Protective gloves.

EN 374.

Material of gloves:

Rubber gloves.

Rubber or other impervious gloves should be worn to prevent skin contact.

Penetration time of glove material:

The exact breakthrough time has to be determined by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses with side shield protection.

EN 166.

Body protection:

Use personal protective equipment as required.

Take off contaminated clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

GENERAL INFORMATION

Appearance:

Form:	Liquid.
Colour:	White.
Odour:	Characteristic.

(Contd. on page 5)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing Date: 31.01.2020

Version Number: 1.0

Revision Date: 31.01.2020

Trade name: RIW FLEXISEAL 500 HG (W)

(Contd. of page 4)

Odour threshold:	Not determined.
pH-value (~):	Not determined.
Change in conditions:-	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	~100 °C
Flash point:	17 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	~430 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	In use, may form flammable/explosive vapour-air mixture.
EXPLOSION LIMITS	
Lower:	2 Vol %
Upper:	13 Vol %
VOC Content:	Not determined.
Vapour pressure:	Not determined.
Density:	Not determined.
Relative density:	~1.1
Vapour density:	Not determined.
Evaporation rate:	Not determined.
Solubility in/Miscibility with:-	
Water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
VISCOSITY	
Dynamic:	Not determined.
Kinematic:	Not determined.
Molecular weight	Not applicable.
9.2 Other information:	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity: Will exothermically polymerise in the presence of initiators.

10.2 Chemical stability: Stable in the presence of inhibitor.

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Susceptible to polymerisation initiated by prolonged storage or the presence of catalyst.

10.4 Conditions to avoid:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials:

Polymerisation catalysts, such as peroxy or azo compounds, strong acids, alkalis and oxidising agents. Oxides and salts of transition metals. Organic Nitrogen containing compounds. Cyclohexanone/Cyclohexenol tautomer.

10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects:

ACUTE TOXICITY Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

38668-48-3 1,1'-(p-tolylimino)dipropen-2-ol

Oral	LD50	25 mg/kg (rat)
------	------	----------------

(Contd. on page 6)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing Date: 31.01.2020

Version Number: 1.0

Revision Date: 31.01.2020

Trade name: *RIW FLEXISEAL 500 HG (W)*

(Contd. of page 5)

Primary irritant effect**Skin corrosion/irritation**

Causes skin irritation.

Serious eye damage/irritation Based on available data, the classification criteria are not met.**Respiratory or skin sensitisation**

May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure**

May cause respiratory irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity:**AQUATIC TOXICITY** No further relevant information available.**12.2 Persistence and degradability:** No further relevant information available.**12.3 Bioaccumulative potential:** No further relevant information available.**12.4 Mobility in soil:** No further relevant information available.**ADDITIONAL ECOLOGICAL INFORMATION****General notes:** Not known to be hazardous to water.**12.5 Results of PBT and vPvB assessment:****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects:** No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods:**Recommendation:**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

UNCLEANED PACKAGING**Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA

UN1866

14.2 UN proper shipping name

ADR, IMDG, IATA

RESIN SOLUTION

(Contd. on page 7)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing Date: 31.01.2020

Version Number: 1.0

Revision Date: 31.01.2020

Trade name: RIW FLEXISEAL 500 HG (W)

(Contd. of page 6)

14.3 Transport hazard class(es)

ADR, IMDG, IATA



Class	3 Flammable liquids.
Label	3

14.4 Packing group

ADR, IMDG, IATA

II

14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user:**Hazard identification number (Kemler code):**

Warning: Flammable liquids.

EMS Number:

33

Stowage CategoryF-E,S-E

B

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not Regulated

Transport/Additional information:**ADR****Limited quantities (LQ)**

5L

Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

Transport category

2

Tunnel restriction code

D/E

IMDG**Limited quantities (LQ)**

5L

Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

See Section 2 for hazard identification.

Directive 2012/18/EU**Named dangerous substances - ANNEX I** None of the ingredients is listed.**Seveso category P5c** FLAMMABLE LIQUIDS**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

H225 Highly flammable liquid and vapour.

H300 Fatal if swallowed.

H315 Causes skin irritation.

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing Date: 31.01.2020

Version Number: 1.0

Revision Date: 31.01.2020

Trade name: *RIW FLEXISEAL 500 HG (W)*

(Contd. of page 7)

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.

Department issuing SDS:

Product Stewardship Department
GCP Applied Technologies
580-581 Ipswich Road,
Slough, Berkshire.
SL1 4EQ

Tel: +44 (0)1753 490 000

Fax: +44 (0)1753 490 001

The first date of preparation: 31.01.2020**Number of revision times and the latest revision date:** 1.0 / 31.01.2020

GB