



DECLARATION OF PERFORMANCE – Sheetseal 9000

1. Identification code: **High Performance Damp Proof Course**
2. Serial number: **Sheetseal 9000**
3. Intended use: **Typically used to prevent water from the ground rising up a wall, deflect water from the inner face of a cavity wall construction to the exterior of the building and to prevent water passing from one part of a wall construction to another.**
4. Manufacturer: **RIW Limited, ARC House, Terrace Road South, Binfield, RG42 4PZ**
5. Authorised representative: **Not applicable, see 4**
6. Assessment and verification of constancy of performance: **System 3**
7. Relevant harmonised standard: **Type A in accordance with EN 14909**
8. European Technical Assessment: **Not applicable**
9. Declared performance

Essential Characteristics	Performance	Harmonised Standard
Reaction to fire	F	EN 14909
Water tightness	Pass	
Resistance to impact	400mm	
Resistance to lower temperature flexibility	-40°C	
Durability against ageing	Pass	
Durability against alkali	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Martin Radford (Business Manager)

